



Safety Shoes 20 kV

NEWPATH



NEWPATH Insulated Shoes 20 kV



Type of constrution

Vulcanized Rubber Sole and Leather

Recommendation

- For working environment with high voltage hazard
- Electrical installations
- Elektrical engineer, chargeman, sub-station handler, power station, operator etc.



New



Compliance

CSA ZA195-02/ASTM F 2413-05 20KV

Electric Shock Resistance (ESR)
Protection Outsole

Sole / Heel

- Electrical shock resistant sole suitable for high voltage environment.
- Fuel oil resistant sole suitable for oily environment.
- Slip resistant.
- Excallent abration resistant for extra durability.
- Heel energy absorption design to minimize the impact to your heel.

Steel Toe Cap

- Non- corrosive coating treatment.
- Meets EN ISO 30345 impact and compression test.
- 200 joule toecap protection.





Safety Shoes 20 kV

RIV



RIV Lineman Insulated Shoes RIV-MV20KV



Type of construction

Vulcanized Rubber Upper and Sole

Recommendation

- For working environment with high voltage hazard
- Electrical installations
- Elektrical engineer, chargeman, sub-station handler, power station, operator etc.

Compliance

CSA ZA195-02/ASTM F 2413-05 20KV

Electric Shock Resistance (ESR)

Protection Outsole.

Working at medium Voltage 20KV, Max Test 35KV




Sole / Heel

- Electrical shock resistant sole suitable for high voltage environment.
- Fuel oil resistant sole suitable for oily environment.
- Slip resistant vulcanized rubber sole.
- Excallent abration resistant for extra durability.
- Heel energy absorption design to minimize the impact to your heel.

Steel Toe Cap

- Non- corrosive coating treatment.
- Meets EN ISO 20345 impact and compression test.
- 200 joule toecap protection.





Safety Shoes 20 kV

Gaston MILLE



LIVE LINE BOOT SPECIAL HAZARD



LIVE LINE BOOT (38/48)
Ref. RRTL3
SB P HRO WRU E FO



ELECTRICAL HAZARD

UP TO 1000V - ASTM F2412-11

ELECTRICAL HAZARD

**INSULATING PENETRATION
RESISTANT MIDSOLE**

ENVIRONMENT

- Special Hazard
- Oil & Gas
- Extreme environment

SOLE

- Textile antiperforation midsole 1 430N
- Extra light PU dual density
- High performance grip: SRC rating
- Auto-cleaning studs

UPPER

- Full grain leather, water & oil resistant (2-2, 2mm thickness)
- Reinforced padding protection of Achilles tendon
- Waterproof tongue & gusset
- Non metallic 240J safety toe (fiberglass)